CARE AND DISINFECTION

TAKE TOGETHER, CARE WE ARE STRONG

These days, it's more important than ever to observe hygiene rules. All JAGUAR products can be cleaned according to these rules. As a basic principle, only use a disinfectant that has been officially approved against viruses (SARS-CoV-2).



SCISSORS

Clean the blades and the pivot area of your JAGUAR scissors with a soft cloth.

Good scissor care (daily cleaning and oiling, safe storage) will extend the lifespan of your scissors and keep them sharper for longer.

If the tension is set correctly, only a minimum amount of pressure is needed to close the scissors (cut). For details of how to check and set the cutting action of your scissors, please see www.jaguarsolingen.en/care-tips.

DISINFECTION

Disinfection bath: The disinfectant should be mixed in the correct concentration, exactly according to the manufacturer's instructions, and then placed in a sufficiently large container with a lid. Then the scissors should be opened and placed inside the bath in such a way that they are completely covered by the liquid (Remove finger ring inserts in advance and clean individually). Put the lid on the container to keep the solution from evaporating. The necessary disinfection time is counted starting from when the last object is placed in the bath. Please see the manufacturer's instructions for the required disinfection time.

Disinfectant residue must always be rinsed off under running water to prevent damaging the scissors. After that, use a hair dryer to blow dry the scissors. Then apply a drop of JAGUAR Maintenance Oil to the pivot area. Wipe the scissors with a soft cloth, spreading any remaining oil all around the scissors (including the cutting edges). Leave the scissors open to dry.

COATED SCISSORS

These scissors can be disinfected with no problem using standard commercially available disinfectants. Simply follow the same steps as for all other scissors (see above)

TCC THE CARECUT®

Before cleaning, always be sure to unplug the device from the power outlet and make sure the scissors have cooled completely. Never immerse the device in water. The device should only be wiped with a slightly damp cloth soaked in soap lotion and then wiped dry with a cloth.

Do not use harsh or corrosive cleaning agents, which could harm the plastic coverings.

SHARPENING SERVICE

We have the very highest standards for the quality and workmanship of our products. Each model requires specific sharpening, as only original sharpening can perfect each pair of scissors. Superior hairdressing scissors require excellent skill and workmanship in repairs and sharpening. Visit our website to learn how you can use our sharpening service.

www.jaguar-solingen.com/en/sharpening



HAIRBRUSH / COMB / HAIR CLIPS

Remove hair and dandruff flakes from brushes and combs (for example with a brush cleaner). Then use a soap solution or a bit of shampoo to clean, rinse in clean water and dry. (Symbol ACHTUNG)



Brushes with natural bristles, rubber cushions or wooden handles can be damaged by disinfection baths. For faster disinfection, spray disinfectant onto the brush and comb and leave on for a certain amount of time according to the manufacturer's instructions.

Disinfectant residue must always be rinsed off under running water to prevent damaging these products. Wipe the brushes and combs with a soft cloth and allow to dry.

ELECTRICAL APPLIANCES



Always be sure to interrupt the supply of electricity by unplugging the JAGUAR electrical appliance from the power outlet before cleaning. Be sure the device has

Never spray an electrical appliance with disinfectant spray or immerse it in a disinfectant solution. Absolutely no disinfectant solution can be allowed to penetrate the inside of hair dryers or straightening irons, as this can create a risk of fire or electric shock. For information on cleaning your electrical appliance, please see the care instructions that came with your device.



HAIRDRYERS

Carefully remove all residual hair from the air filter grille. Free movement of air must be ensured. If the air filter is blocked, the heating can overheat and burn through.

Disinfect the housing of the hair dryer with a slightly damp cloth soaked in grease-dissolving household cleaner and then wipe with a dry cloth.



STRAIGHTENING IRONS / CURLERS

Clean the plates with a slightly damp cloth and wipe off with a disinfectant solution listed by the Association for Applied Hygiene (VAH). Disinfect the housing with a slightly damp cloth soaked in soap lotion and then wipe with a dry cloth.



RAZOR

Use a soft cloth to remove hair from the hair shaper. Razor blades should be changed and disposed of after every treatment.

The hair shapers can be placed in a disinfection bath to disinfect. (Also see disinfection bath instructions for scissors.)





HAIR CLIPPERS

To keep your hair clippers running and cutting with optimum performance, daily care is a must. Battery performance is severely restricted if there is any residual hair buildup on the clippers.

- Clean the cutting plate with the cleaning brush.
- If possible, remove the entire cutting head and clear out any hair residue from underneath.

Oiling: The blade head should be oiled daily. Please be sure to use only the oil included with your product or a special oil for clippers.

- 5-drop principle: Angle the clipper slightly and place three drops along the cutting plate from the front and one drop on each side
- To make sure the oil can spread effectively, run the JAGUAR clipper for about 20 seconds, allowing excess oil to drip onto a towel.

DISINFECTION

Spray disinfecting spray onto the cutting plates from a very close distance. Leave on for a certain amount of time according to the manufacturer's instructions and wipe off with a soft cloth. Alternatively, the frontal area of the cutting plate (only the area with the teeth!) can be held in a disinfectant solution for a brief time. Then wipe off with a soft cloth (neutralize) and dry.



Never spray a clipper with disinfectant spray or immerse it in a disinfectant solution. The cutting head should also never be placed fully in a disinfectant bath. The eccentric connector and plastic mechanics have been coated with a permanent lubricant that would be removed if this item were immersed.